ATTACHMENT "A"

Loaned extinguishers shall be provided at no charge for each extinguisher removed for repair or inspection. The loaner shall be of same type and size.

National Fire Protection Association (NFPA) verification collars are required.

Annual service inspections will be upon request of Milwaukee County and shall include but not be limited to the following:

_ Remove and Check Hose or Discharge	Clear Hose Flex and Check Hose Inspect Hose or Nozzle for Damage Check Couplings Check Bracket Attach New Tag Check Discharge Valve Remove and Check Pull-pin Check Cam Lock Adjustment Change Seal
Check Shell Repaint Small Scratches Inspect Hanger Attachment Clear Unit Check Dates for Internal & Hydrostatic Retest Check Nozzle/Hose or Discharge Nozzle Remove and Check Hose or Discharge	Inspect Hose or Nozzle for Damage Check Couplings Check Bracket Attach New Tag Check Discharge Valve Remove and Check Pull-pin Check Cam Lock Adjustment
Repaint Small Scratches Inspect Hanger Attachment Clear Unit Check Dates for Internal & Hydrostatic Retest Check Nozzle/Hose or Discharge Nozzle Remove and Check Hose or Discharge	Check Couplings Check Bracket Attach New Tag Check Discharge Valve Remove and Check Pull-pin Check Cam Lock Adjustment
Inspect Hanger Attachment Clear Unit Check Dates for Internal & Hydrostatic Retest Check Nozzle/Hose or Discharge Nozzle Remove and Check Hose or Discharge	_ Check Bracket _ Attach New Tag _ Check Discharge Valve _ Remove and Check Pull-pin _ Check Cam Lock Adjustment
Clear Unit Check Dates for Internal & Hydrostatic Retest Check Nozzle/Hose or Discharge Nozzle Remove and Check Hose or Discharge	Attach New Tag _ Check Discharge Valve _ Remove and Check Pull-pin _ Check Cam Lock Adjustment
Check Dates for Internal & Hydrostatic Retest Check Nozzle/Hose or Discharge Nozzle Remove and Check Hose or Discharge	_ Check Discharge Valve _ Remove and Check Pull-pin _ Check Cam Lock Adjustment
Hydrostatic Retest Check Nozzle/Hose or Discharge Nozzle Remove and Check Hose or Discharge	Remove and Check Pull-pin Check Cam Lock Adjustment
_ Check Nozzle/Hose or Discharge Nozzle _ Remove and Check Hose or Discharge	_ Check Cam Lock Adjustment
_ Remove and Check Hose or Discharge	
_ Remove and Check Hose or Discharge	Changa Saal
	_ Change Seal
Nozzle	_ Clean Handle and Lever
_ Hydro units requiring testing, when returned to the shop we will receive free loaners On the spot service for recharge and internal inspection _ The following services are required for each test: - Conduct a full discharge test - Siphon tube from valve - Check for damage - Clear tube - Check proper length	_ Valve Service _ Clean and Check Stem Shaft O-Ring _ Clean O-Ring groove _ Clean valve stem _ Clean spring _ Lubricate O-Rings and stem _ Clean and check valve body threads _ Clean vent hole _ Shell- interior inspection _ Empty contents _ Inspect by suitable light _ Clean seams and check _ Clean and examine neck threads _ Reassemble and leak test. Recharge